

PGV650P VERTICAL BALING PRESS

Baling press for economical operation

PGV Range

The range of PGV balers are ideally suited for baling materials such as cardboard, plastic packaging, textiles and dry general wastes.

Each has been designed to ensure you achieve maximum performance and reliability, with ease of operation.



BENEFITS:

- Save Money; generate additional revenue for your business
- Save Time; no need to load skips or bins
- Save Space; less skips required as the volume of waste can be reduced by 95%
- Save the environment
- Improve Health & Safety

SAFETY:

All Dicom Brand products are designed and manufactured with operator safety our highest priority.

Each baler comes fully compliant to all current Safety Standards and CE Marked.

During installation full safety and certified operator training is provided by our highly experienced installation and service engineers.

Equipment is supplied with the following standard safety features :

- Emergency Stop
- 24 Volt controls
- Dual safety switches
- Dual channel safety relays
- Operator manuals supplied


Technical Data and Measurements

Platen Force	35 tonne	Motor Size	5.5 kW
Cycle Time (Seconds)	38	Control Voltage	24v
Bale Width	1520	Bale Depth	810
Bale Height	1000	Bale Ties	6 x (wire or tape)
Bale Weight	Up to 650 kgs		
Electrical Supply Requirements	16A 415V 3-phase with neutral and earth. Protection via Type "D" circuit breaker or Motor rated fuses		

Dimensions in mm

A Overall Width	2032
C Overall Height	3515
E Bale Chamber Depth	812
G Load Opening Width	1520
I Bale Door Clearance	1550

B Overall Depth	1235
D Feed Height	1200
F Bale Chamber Height	1050
H Load Opening Height	680



www.kadantpaal.com

